

PRODUCT DESCRIPTION

Corton is a new interpretation of a natural stone from France, maintaining its characteristic rosy beige colour with subtle grey veins lightly dotted with pink and orange. Recommended for use on floors and walls in homes and public spaces, it is available with three surface finishes: Natural and Ancient Honed.

Corton is made in the Viano (RE) plant, which has an ISO 14001 certified environmental management system and an ISO 9001 certified quality management system. The product is guaranteed ecological thanks to ANAB certification.

TECHNICAL SPECIFICATIONS

Coverings (for indoor and outdoor walls and floors) are made up of first choice tiles in the 60x60, 60x30 and 30x30 formats, 11 mm thick.

Surface finishes are Matt or Ancient honed. The tiles all have the same gauge and are perfectly squared off and ground.

The material, made out of a mixture of noble clays fired at 1300 °C, is even throughout its entire thickness, compact and resistant to frost and temperature excursions, flexing and chemical aggression.

The material is highly ecological.

TECHNICAL FEATURES

Product:	Fine vitrified porcelain stoneware
Underside of tile:	the pattern in relief guarantees perfect adhesion to the floor or wall substrate. This improves quality and guarantees economical laying.

Water absorption	ISO 10545-3	0,04%
Sizes	ISO 10545-2	±0,2% Length and width ±5% Thickness ±0,2% Linearity ±0,2% Wedging ±0,2% Warpage
Flexion resistance	ISO 10545-4	52 mm ²
Deep abrasion resistance	ISO 10545-6	112 mm ³
Frost resistance	ISO 10545-12	Frost-proof
Coefficient of linear thermal-expansion	ISO 10545-8	6,2x10 ⁻⁶ °C ⁻¹
Thermal shock resistance	ISO 10545-9	Resistant
Color resistance to light	DIN 51094	Resistant
Chemical resistance	ISO 10545-13	Resistant
Friction coefficient (slipperines)	ASTM C 1028	>0,60

CLEANING AND MAINTENANCE

Cleaning after laying

Use acidic products to eliminate all residues of glue, mortar and cement. Rinse well.

Daily maintenance

Ordinary cleaning should be done using clean warm water with a cleaning product such as Emulsio Ceramica, Lysoform Casa, Aiax or Fila Cleaner diluted according to the instructions provided and a microfibre cloth. On structured surfaces such as bush-hammered and chiselled finishes, it is advisable to use a rough cloth. No special treatments are required.